



# RAD15 SONIC 1.5

1.5" RECESSED LED DOWNLIGHT



## FEATURES

- Air-tight and wet location approved
- Type IC rated - approved for direct contact with insulation
- Quick connect wire allows for efficient installation
- Spring loaded mounting clips
- Isolated driver inside junction box
- New construction plate available (NCH150)
- Optional Emergency Backup
- 5 Year Warranty

## SPECIFICATIONS

Wattage	7W	Dimming	5% - 100% Triac / 0-10V
Lumens (Delivered)	600LM	Environment	IP65 Wet Location
Input Voltage	120 / 277V	Material	Aluminum Body with Anodized Heat Sink
CCT	27K/ 30K/ 35K / 40K	Operating Temperature	-4°F - 104°F
Efficacy	>82LM/W	Lamp Life	50,000 hrs
CRI	>90	Cut Out	2"
Beam Angle	38°		



PROJECT:

PREPARED BY:

TYPE:



# RAD15 SONIC 1.5

1.5" RECESSED LED DOWNLIGHT

## ORDERING GUIDE

RAD15 - \_\_\_\_ - 7 - \_\_\_\_ - \_\_\_\_ - 38 - \_\_\_\_ - \_\_\_\_ *Example: RAD15-R-7-27-120-38-HX-WT-EM*

Model	Wattage	Color Temperature	Input Voltage	Beam Angle	Trim Finish	EM
<b>RAD15R</b> (Round)	<b>7</b> 7W (600LM)	<b>27</b> 2700K	<b>120</b> 120V (Triac)	<b>38</b> 38°	<b>WT</b> White	None (Leave Blank)
<b>RAD15S</b> (Square)		<b>30</b> 3000K			<b>277</b> 277V (0-10V)	
		<b>35</b> 3500K			<b>BN</b> Brushed Nickel	
		<b>40</b> 4000K			<b>GD</b> Gold	
					<b>CP</b> Copper	

## NEW CONSTRUCTION HOUSING


Model	Description
NCH150	New Construction Housing Plate




# RAD15 SONIC 1.5

1.5" RECESSED LED DOWNLIGHT

## DIMENSIONS



## LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






# RAD15 SONIC 1.5

1.5" RECESSED LED DOWNLIGHT

## ACCESSORIES

### NEW CONSTRUCTION MOUNTING PLATE NCH150

- Constructed out of galvanized steel
- Magnetic plate and driver facilitate easy and secure placement





# RAD15 SONIC 1.5

1.5" RECESSED LED DOWNLIGHT

## TRIM COLOR OPTION

White	WT
Black	BK
Brushed Nickel	BN
Gold	GD
Bronze	BZ
Copper	CP



Existing Trim



RAD15R-BK



RAD15R-BN



RAD15R-GD



RAD15R-BZ



RAD15R-CP



Existing Trim



RAD15S-BK



RAD15S-BN



RAD15S-GD



RAD15S-BZ



RAD15S-CP



# RAD15 SONIC 1.5


1.5" RECESSED LED DOWNLIGHT

## EMERGENCY BACK UP DRIVER

### RAD15-EM

90 minute run time

See spec sheet for further information





# RAD15 SONIC 1.5

1.5" RECESSED LED DOWNLIGHT

## COMPATIBLE DIMMERS

LUTRON	LOAD (W)
SKYLARK CONTOUR LECL-153P	150W
SKYLARK CONTOUR CTCL-150H	150W
SKYLARK CONTOUR LGCL-153PLH	150W
SKYLARK CONTOUR CTCL-153P	150W
SKYLARK CONTOUR SCL-153P	150W
SKYLARK CONTOUR S-600P	600W
CASETA PD-6WCL	600W
CASETA PD-5NE	150W
CASETA PD-10NXD	250W
DIVA DVCL-153P	150W
TOGLER TGGL-153P	150W
ARIADNI AYCL-153P	150W
MAESTRO MACL-153M	150W

LUTRON	LOAD (W)
ILLUMATEC IPL06	150W
SURESLIDE 6672	150W
SURESLIDE 6674	150W

EATON	LOAD (W)
SMART DIMMER AAL06	300W

PASS & SEYMOUR	LOAD (W)
HARMONY DCL453PTCCCV6	150W

GE	LOAD (W)
ROCKER 10464	150W
TOGGLE 18027	150W