





ANCHOR PLUS WALL WASHER

TERRAIN SERIES



The Anchor Wall Wash Linear is versatile outdoor lighting fixture that combines efficiency and aesthetics, illuminating outdoor space with precision while enhancing architectural features and creating captivating wall wash effects. Its durable construction and weather resistance make it suitable for range of applications, from building facades and landscape to walkways and plazas, providing a versatile light solution for transforming outdoor environment into visually stunning space.

FEATURES

- Multiple lengths available
- Powder coated aluminum body
- 12 watt per foot
- ETL listed
- Universal Voltage
- 5 Year warranty

SPECIFICATIONS

Color Temperature	2700K, 3000K, 4000K, 5000K, 6000K	Input Voltage	100-277V
Length	1FT, 2FT, 4FT	Cover	Silk screen tempered glass
Optics	10°, 25°, 35°, 50°, 15°x40°	Surface Finishing	Power Coat
Wattage	12W/FT	Power Factor	>0.9
Lumens	100LM/W	Storage Temperature	-30°C to 60°C
Dimming	ON-OFF, 0-10V, DALI	Operating Temperature	-10°C to 50°C
Housing Material	high density extruded aluminum alloy	Ingress Protection Rating	IP66
Lens Material	Optical grade PMMA	Certification	ETL
		IK Rating	IK08





ARKP ANCHOR PLUS WALL WASHER

TERRAIN SERIES

ORDERING GUIDE

ARKP- _____ - _____ - UNV - _____ - _____ - _____

Example: ARKP-1-27K-010-13-AG

Model	Length	CCT	Voltage	Dimming	Optics	Finish	
ARKP	1 1FT	27 2700K	100-277V	0-10 0-10V	10 10 Degree	CG Gray (Power Coat)	
	2 2FT	30 3000K		DI Dali	25 25 Degree	BK Black (Power Coat)	
	4 4FT	35 3500K		OF ON/OFF	35 35 Degree	50 50 Degree	WT White (Power Coat)
		40 4000K					
		50 5000K					
		60 6000K					
	WW 15x40 Wall Wash						

**This is made to order item, please contact for lead time*

OPTICS AND MOUNTING ORDERING GUIDE

ARKP- _____ - _____

Example: ARKP-AAGL-1

Model	Length	Description
ARKP-AAGL	1 1FT	Asymmetric anti-glare louver
ARKP-SAGL	2 2FT	Symmetric anti-glare louver
ARKP-M	4 4FT (For wall mount leave blank)	Adjustable wall mount bracket

**This is made to order item, please contact for lead time*

WIRING ACCESSORY ORDERING GUIDE

ARKP- _____


Example: ARKP-PL-1

Model	Description	Model	Description
ARKP-PL-1	Power Lead - 11.8in	ARKP-PLDL-1	Power and signal data lead combined - 11.8in
ARKP-PL-6	Power Lead - 78.7in	ARKP-PLDL-6	Power and signal data lead combined - 78.7in
ARKP-PL-20	Power Lead - 236.2in	ARKP-PLDL-20	Power and signal data lead combined - 236.2in
ARKP-PL-50	Power Lead - 590.5in	ARKP-PLDL-50	Power and signal data lead combined - 590.5in
ARKP-PE-1	Coupling power extension - 11.8in	ARKP-PEDL-1	Power and data combined extension - 11.8in
ARKP-PE-2	Coupling power extension - 23.6in	ARKP-PEDL-2	Power and data combined extension - 23.6in
ARKP-PE-6	Coupling power extension - 71in	ARKP-PEDL-6	Power and data combined extension - 71in
ARKP-DL-1	Data lead - 11.8in	ARKP-LJ-T	Leading T-Joint
ARKP-DL-6	Data lead - 78.7in	ARKP-PL	Coupling with power for home run (power injector)
ARKP-DL-20	Data lead - 236.2in	ARKP-EC	End cap for power loop out
ARKP-DL-50	Data lead - 590.5in	ARKP-EC-D	End cap for power loop out

**This is made to order item, please contact for lead time*



DIMENSIONS





CABLE CONDUCTOR SPECIFICATIONS

The core in the power and data cable are colored according to the following table:

Cable	Function	Core (US)	Wire Size
Power lead in/ Power extension Cable	L (live)	Black	16AWG
	N (Netural)	White	16AWG
	GND (Earth)	Green	16AWG
Data lead in	DIM+	Purple	20AWG
	DIM-	Pink	20AWG
	N/A	Yellow	20AWG
Power and Data lead in/ Power data extension cable	L (live)	Black	16AWG
	N (Netural)	White	16AWG
	GND (Earth)	Green	16AWG
	DIM+	Purple	22AWG
	DIM-	Pink	22AWG
	N/A	Yellow	22AWG



The maximum number of connected fixtures in a daisy chain:

Power/ft	Region	Main Voltage	Cable Max. power	Max. no. of 4ft fixtures can be clusted
12W	US	120V	1020W	21 nos.




ARKP ANCHOR PLUS WALL WASHER TERRAIN SERIES

ANTI-GLARE ACCESSORIES



ARKP-AAGL
Asymmetric anti-glare louver


Height with and without mounting bracket



ARKP-SAGL
Symmetric anti-glare louver

Height with and without mounting bracket

MOUNTING BRACKET



ARKP-M



ARKP ANCHOR PLUS WALL WASHER

TERRAIN SERIES


WIRING GUIDE FOR ON/OFF

Power



Product Image	Model	Length	Description	Cable End		Conductor Size
	ARKP-PL-1	11.8	Power Lead (ON/OFF)	Female	Bare Wire	3x16AWG
	ARKP-PL-6	78.7				
	ARKP-PL-20	236.2				
	ARKP-PL-50	590.5				

Coupling for Daisy Chain



Product Image	Model	Length	Description	Cable End		Conductor Size
	ARKP-PE-1	11.8	Power Extension (ON/OFF)	Female	Male	3x16AWG
	ARKP-PE-2	23.6				
	ARKP-PE-6	71				
	ARK-EC		ON/OFF			




ARKP ANCHOR PLUS WALL WASHER

TERRAIN SERIES

WIRING GUIDE FOR 0-10V/DALI

Leading wiring option one: (0-10V / Dali)

Description: Leading T joint with power and data leading cables



Product Image	Model	Length	Description	Cable End		Conductor Size
	ARKP-PL-1	11.8	Power Lead (ON/OFF)	Female	Bare Wire	3x16AWG
	ARKP-PL-6	78.7				
	ARKP-PL-20	236.2				
	ARKP-PL-50	590.5				
	ARKP-DL-1	11.8	Data Lead (0-10V, DALI)	Female	Bare Wire	3x20AWG
	ARKP-DL-6	78.7				
	ARKP-DL-20	236.2				
	ARKP-DL-50	590.5				
	ARKP-LJ-T		Leading T-Joint (0-10V, DALI)			



Product Image	Model	Length	Description	Cable End		Conductor Size
	ARKP-PLDL-1	11.8	Power & Signal Data Lead (0-10V, DALI) Combined	Female	Bare Wire	3x16AWG + 3x22AWG
	ARKP-PLDL-6	78.7				
	ARKP-PLDL-20	236.2				
	ARKP-PLDL-50	590.5				



ARKP ANCHOR PLUS WALL WASHER


TERRAIN SERIES

COUPLING FOR DAISY CHAIN



Power injection one:

Description: Power injection with power leading cable



Product Image	Model	Length	Description	Cable End		Conductor Size
				Female	Male	
	ARKP-PEDL-1	11.8	Power and Data Combined extension (0-10V, DALI)	Female	Male	3x16AWG + 3x22AWG
	ARKP-PEDL-2	23.6				
	ARKP-PEDL-6	71				
	ARKP-PL		Power Injector (0-10V, DALI)			
	ARKP-EC-D		End cap for Power loop out (0-10V, DALI)			