


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 97.66 lm/W			
MODEL	3500K	I _{max} (cd)	411.2	S/MH(C0/180)	1.31
NOMINAL POWER(W)	14	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1338.5	η UP,DN(C0-180)	0.0,49.8
NOMINAL FLUX(lm)	1338.5	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.2
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	η down(%)	100.0	CIBSE SHR MAX	1.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	404.7	403.8	405.5	404.6	405.8	404.1	404.8	403.5	0- 10	38.87	38.87	2.9,2.9
20	387.4	384.7	384.6	386.0	387.5	384.7	382.9	384.1	10- 20	111.9	150.8	11.3,11.3
30	360.3	354.5	354.0	356.6	361.1	354.6	351.3	353.7	20- 30	171.3	322.0	24.1,24.1
40	325.2	316.6	310.4	318.2	326.6	316.3	307.9	315.2	30- 40	211.0	533.0	39.8,39.8
50	282.5	269.0	256.1	270.9	284.6	269.9	254.2	268.4	40- 50	226.5	759.6	56.7,56.7
60	234.1	214.7	191.5	215.8	236.8	216.3	191.0	214.4	50- 60	216.4	975.9	72.9,72.9
70	180.9	156.6	119.5	157.8	184.8	158.9	120.2	156.8	60- 70	182.7	1159	86.6,86.6
80	127.3	98.96	47.82	98.79	130.5	102.1	51.79	101.3	70- 80	130.5	1289	96.3,96.3
90	32.36	0	0	0	49.13	0	0	0	80- 90	49.42	1339	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 645.97 lm

%lum = 48.3%

%lamp = 48.3%

Conical surface Flux(120deg): 975.94 lm

%lum = 72.9%


%lamp = 72.9%

H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	116287	0
80	73330	27539
75	59530	32332
70	52894	34951
65	49029	36800
60	46816	38302
55	45118	39018
50	43948	39840
45	43091	40054


H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.02	.97	.93	.90	.95	.91	.95	.92	.88	.91	.88	.86	.88	.85	.83	.81
2.0	.88	.80	.74	.86	.79	.73	.82	.76	.71	.79	.74	.70	.76	.72	.68	.66
3.0	.76	.68	.61	.75	.67	.60	.72	.65	.59	.69	.63	.58	.66	.61	.57	.55
4.0	.67	.58	.51	.66	.57	.50	.63	.56	.50	.61	.54	.49	.59	.53	.48	.46
5.0	.60	.50	.43	.59	.50	.43	.57	.49	.43	.55	.48	.42	.53	.47	.42	.39
6.0	.54	.44	.38	.53	.44	.37	.51	.43	.37	.49	.42	.37	.48	.41	.36	.34
7.0	.49	.39	.33	.48	.39	.33	.46	.38	.33	.45	.38	.32	.43	.37	.32	.30
8.0	.44	.35	.29	.44	.35	.29	.42	.35	.29	.41	.34	.29	.40	.33	.29	.27
9.0	.41	.32	.26	.40	.32	.26	.39	.31	.26	.38	.31	.26	.37	.30	.26	.24
10.0	.37	.29	.24	.37	.29	.24	.36	.29	.24	.35	.28	.23	.34	.28	.23	.22



H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.347	.197	.063	.340	.194	.062	.326	.187	.060	.314	.181	.058	.303	.175	.057		
2.0	.317	.174	.053	.311	.171	.053	.299	.166	.052	.288	.162	.051	.278	.157	.050		
3.0	.289	.154	.046	.283	.152	.046	.273	.148	.045	.263	.144	.044	.254	.140	.043		
4.0	.263	.137	.040	.258	.135	.040	.249	.132	.039	.240	.129	.039	.232	.126	.038		
5.0	.241	.123	.036	.237	.122	.035	.229	.119	.035	.221	.117	.035	.214	.114	.034		
6.0	.222	.112	.032	.219	.110	.032	.211	.108	.031	.204	.106	.031	.198	.104	.031		
7.0	.206	.102	.029	.203	.101	.029	.196	.099	.029	.190	.097	.028	.184	.096	.028		
8.0	.192	.094	.026	.189	.093	.026	.183	.091	.026	.177	.090	.026	.172	.088	.026		
9.0	.179	.087	.024	.176	.086	.024	.171	.084	.024	.166	.083	.024	.161	.082	.024		
10.0	.168	.080	.022	.165	.080	.022	.161	.079	.022	.156	.077	.022	.152	.076	.022		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.183	.156	.131	.156	.134	.113	.107	.092	.078	.062	.053	.045	.020	.017	.015	
2.0	.176	.132	.095	.150	.113	.082	.103	.078	.057	.059	.046	.034	.019	.015	.011	
3.0	.168	.114	.072	.144	.099	.062	.099	.069	.044	.057	.040	.026	.018	.013	.008	
4.0	.160	.101	.056	.138	.088	.049	.095	.061	.034	.055	.036	.020	.018	.012	.007	
5.0	.153	.091	.046	.131	.079	.040	.090	.055	.028	.052	.032	.017	.017	.011	.005	
6.0	.145	.083	.038	.125	.072	.033	.086	.050	.023	.050	.029	.014	.016	.010	.005	
7.0	.138	.076	.032	.119	.066	.028	.082	.046	.020	.048	.027	.012	.015	.009	.004	
8.0	.131	.070	.028	.113	.061	.024	.078	.043	.017	.046	.025	.010	.015	.008	.003	
9.0	.125	.065	.025	.108	.057	.021	.075	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.119	.061	.022	.103	.053	.019	.071	.037	.014	.042	.022	.008	.013	.007	.003	

H(β) Range:-90 - 90DEG
 H(β) Interval: 0.2DEG
 Test Speed: MEDIUM
 Temperature:25.3DEG
 Operators:Q
 Test Date:2021-01-25

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:9.900m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm										
NAME: LB53291					TYPE:LED Strip LIGHT			WEIGHT:		
SPEC.:1000*10MM					DIM.: 1000*10MM			SERIAL No.:1		
MFR.: LIGHT BLUE USA					SUR.:1000*10MM			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.3	26.9	25.6	27.1	27.3	24.5	26.1	24.7	26.3	26.5
3H	27.5	29.0	27.8	29.2	29.5	26.0	27.5	26.3	27.7	28.0
4H	28.6	30.0	28.9	30.3	30.6	26.7	28.1	27.0	28.3	28.6
6H	29.6	31.0	30.0	31.3	31.5	27.1	28.4	27.4	28.7	29.0
8H	30.1	31.4	30.5	31.7	32.0	27.1	28.4	27.5	28.7	29.0
12H	30.7	31.9	31.0	32.2	32.5	27.1	28.4	27.5	28.7	29.0
4H 2H	26.0	27.4	26.3	27.6	27.9	25.3	26.7	25.6	27.0	27.3
3H	28.4	29.6	28.8	29.9	30.3	27.1	28.4	27.5	28.7	29.0
4H	29.7	30.8	30.0	31.1	31.5	27.9	29.1	28.3	29.4	29.7
6H	30.8	31.9	31.2	32.2	32.6	28.5	29.5	28.9	29.9	30.2
8H	31.4	32.4	31.8	32.7	33.1	28.6	29.6	29.0	29.9	30.3
12H	32.0	32.9	32.5	33.3	33.7	28.6	29.5	29.0	29.9	30.3
8H 4H	30.0	31.0	30.4	31.4	31.7	28.6	29.5	29.0	29.9	30.3
6H	31.5	32.3	31.9	32.7	33.1	29.4	30.2	29.9	30.6	31.1
8H	32.2	32.9	32.7	33.3	33.8	29.6	30.3	30.1	30.8	31.2
12H	33.0	33.6	33.5	34.1	34.6	29.6	30.2	30.1	30.7	31.2
12H 4H	30.1	30.9	30.5	31.3	31.7	28.7	29.6	29.1	30.0	30.4
6H	31.6	32.3	32.0	32.7	33.2	29.7	30.4	30.2	30.9	31.3
8H	32.4	33.0	32.9	33.5	34.0	30.0	30.6	30.4	31.0	31.5
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1				
1.5H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
2.0H	+ 0.2 / - 0.3					+ 0.1 / - 0.3				

CIE Pub.117, 1339 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 1.0$)
Area: 0.01 m²

H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	55	43	36	54	43	36	53	42	35	29
0.80	65	53	45	64	52	45	62	51	44	37
1.00	73	61	53	72	61	53	69	62	53	45
1.25	80	69	61	79	68	61	76	67	60	52
1.50	85	75	67	84	74	66	80	72	65	57
2.00	92	83	76	91	82	75	87	80	74	65
2.50	97	88	81	94	87	81	91	84	79	70
3.00	100	93	86	98	91	85	94	88	83	74
4.00	105	98	93	102	96	92	98	93	89	80
5.00	107	102	97	105	100	96	100	96	93	83
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 0.2DEG
 Test Speed: MEDIUM
 Temperature:25.3DEG
 Operators:Q
 Test Date:2021-01-25

$V(B)$ Range:-80 - 80DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:9.900m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:

Flux out:934.7 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range: -90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature: 25.3DEG
Operators: Q
Test Date: 2021-01-25

V(B) Range: -80 - 80DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity: 65.0%
Test Distance: 9.900m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	49493
L_0~180(75)av	60251
L_0~180(85)av	117335
L_90~270(65)av	36811
L_90~270(75)av	32780
L_90~270(85)av	0
L_45(65)av	44108
L_45(75)av	49528
L_45(85)av	39775

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
 H(β) Interval: 0.2DEG
 Test Speed: MEDIUM
 Temperature:25.3DEG
 Operators:Q
 Test Date:2021-01-25

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:9.900m [K=1.0000]
 Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:

Table--1

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:

Table--2

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:

Table--3

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.000V I:0.5711A P:13.706W PF:1.0000 Freq:50.00Hz Lamp Flux:1338.5x1 lm		
NAME: LB53291	TYPE:LED Strip LIGHT	WEIGHT:
SPEC.:1000*10MM	DIM.: 1000*10MM	SERIAL No.:1
MFR.: LIGHT BLUE USA	SUR.:1000*10MM	Shielding Angle:

Table--4

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 0.2DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:Q
Test Date:2021-01-25

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.421
Humidity:65.0%
Test Distance:9.900m [K=1.0000]
Remarks: