



INFUSE SERIES SURFACE CYLINDER ROUND

RAYHIL X INPUT



FEATURES

- Universal Voltage
- Triac and 0-10 Dimming
- Multiple Finish combinations
- Wattage and CCT Selectable
- Interchangeable components
- Designed by Input

SPECIFICATIONS

Wattage	6W/9W/12W Selectable
Lumens	80LM/W
Color Temperature	2700K/3000K/3500K/4000K/5000K
CRI	80
Dimming	Triac/0-10V
Light Source	Integrated LED
Voltage	UNV 110-277
Base	Black/White
Trim	Black/White/Brass/Wood
Environment	Damp
Certification	ETL/ES
Dimension	4.5"W x 8.625"H x 2.5"D
Material	Aluminum
Application	Surface

ORDERING GUIDE

INFP - RD - CCT - _____ - _____ - _____

Example: INFS-RD-CCT-BK-BK-RD

Model	Shape	Wattage	Lumens (Delivered)	CCT
INFS	RD Round	6W/9W/12W Selectable	480LM/720LM/960LM	CCT 27K/30K/35/40K/50K Selectable
Base	Trim	Canopy		
BK Black	BK Black	RD Round		
WT White	WT White	SQ Square		
CS Custom (Contact for requirements)	BR Brass			
	WD Wood			
	CS Custom (Contact for requirements)			

PROJECT:

PREPARED BY:

TYPE:



INFUSE SERIES SURFACE CYLINDER ROUND

RAYHIL X INPUT

FINISH

White Base



White trim



Black trim



Brass trim



Wood trim

Black Base



White trim



Black trim



Brass trim



Wood trim

Custom Finish


Custom finish requests are available for both Base and Trim



INFUSE SERIES SURFACE CYLINDER ROUND

RAYHIL X INPUT

DIMENSIONS





INFUSE SERIES SURFACE CYLINDER ROUND

RAYHIL X INPUT

Interchangeable Components

