



INFUSE SERIES WALL CYLINDER SQUARE

RAYHIL X INPUT



FEATURES

- Universal Voltage
- Triac and 0-10 Dimming
- Multiple Finish combinations
- Wattage and CCT Selectable
- Customized Signage and Braille Options
- Interchangeable components
- Designed by Input

SPECIFICATIONS

Wattage	6W/9W/12W Selectable
Lumens	80LM/W
Color Temperature	2700K/3000K/3500K/4000K/5000K
CRI	80
Dimming	Triac/0-10V
Light Source	Integrated LED
Voltage	UNV 110-277
Base	Black/White
Trim	Black/White/Brass/Wood
Environment	Damp
Certification	ETL/ES
Dimension	5"W x 12.375"H x 2.125"D
Material	Aluminum
Application	Wall Mount

ORDERING GUIDE

INFW - SQ - CCT - _____ - _____ **Example: INFS-SQ-CCT-BK-BK**

Model	Shape	Wattage	Lumens (Delivered)	CCT
INFW	SQ Square	6W/9W/12W Selectable	480LM/720LM/960LM	CCT 27K/30K/35/40K/50K Selectable
Base	Trim	Signage		
BK Black	BK Black	Contact for Customized Signage and Braille Options		
WT White	WT White			
CS Custom	BR Brass			
(Contact for requirements)	WD Wood			
	CS Custom			
	(Contact for requirements)			



INFUSE SERIES WALL CYLINDER SQUARE

RAYHIL X INPUT

FINISH

White Base



White trim



Black trim



Brass trim



Wood trim

Black Base



White trim



Black trim



Brass trim



Wood trim

Custom Finish


Custom finish requests are available for both Base and Trim



INFUSE SERIES WALL CYLINDER SQUARE

RAYHIL X INPUT

DIMENSIONS





INFUSE SERIES WALL CYLINDER SQUARE

RAYHIL X INPUT

Interchangeable Components

