PROJECT: PREPARED BY: TYPE:



### F21

## FLORA CIRCULAR IN-WALL

TERRAIN SERIES



#### **FEATURES**

- 30 Degree Beam Angle
- Aluminum Body

- IK06 Rating
- Wall Application

#### **SPECIFICATIONS**

3W	LED	CREE XPE LED
130LM	Housing	Powder coated in black aluminium
DC 24V	Trim	Powder coated in black aluminium
2700K/3000K/4000K	Cut Out	2.4"
80+	Dimension	2.7" D x 1.35" H
30°	Driver	Remote Power Supply
Non-Dimmable	Accessories	Mounting Sleeve Included
IP65	Warranty	5 Years
IK06	Certification	CE, RoHS
	130LM DC 24V 2700K/3000K/4000K 80+ 30° Non-Dimmable IP65	130LM Housing DC 24V Trim 2700K/3000K/4000K Cut Out 80+ Dimension 30° Driver Non-Dimmable Accessories IP65 Warranty

#### **ORDERING GUIDE**

F21 - 3 - - 120 - BK **Example: F21-3-27-120-BK** 

Model	Wattage	Color Temp.	Optics	Finish	Optional Accessories
F21		<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K	<b>120</b> 120°	<b>BK</b> Black	Installation Sleeve (Included with fixture)

QUICKSHOP OPTION: F21-3-30-120-BK







PROJECT: PREPARED BY: TYPE:





# FLORA CIRCULAR IN-WALL


TERRAIN SERIES

F21

#### **DIMENSIONS**







REVISION DATE 10/30/2024 TELEPHONE: 212.931.1230 SUPPORT@RAYHIL.COM WWW.RAYHIL.COM

PROJECT: PREPARED BY: TYPE:



## FLORA CIRCULAR IN-WALL

TERRAIN SERIES

F21

#### NON-DIMMABLE DRIVERS



Model LB55504
Wattage 60W
Dimensions 7.4" x 3.6" x 1.02"
Temperature IP20
Dimming Non-Dimmable



Model LB55450
Wattage 120W
Dimensions 8.66" x 3.6" x 1.61"
Temperature IP20
Dimming Non-Dimmable



Model LB55451
Wattage 200W
Dimensions 10.23" x 4.05" x 1.81"
Temperature IP20
Dimming Non-Dimmable

\*Flora Landscape Light Fixture are not compatible with Dimmable Drivers

REVISION DATE 10/30/2024 TELEPHONE: 212.931.1230 SUPPORT@RAYHIL.COM WWW.RAYHIL.COM