PROJECT: PREPARED BY: TYPE:



F21

FLORA CIRCULAR IN-WALL

TERRAIN SERIES



FEATURES

- 30 Degree Beam Angle
- Aluminum Body

- IK06 Rating
- Wall Application

SPECIFICATIONS

Wattage	3W	LED	CREE XPE LED
Lumens	130LM	Housing	Powder coated in black aluminium
Input Voltage	DC 24V	Trim	Powder coated in black aluminium
CCT	2700K/3000K/4000K	Cut Out	2.4"
CRI	80+	Dimension	2.7" D x 1.35" H
Beam Angle	30°	Driver	Remote Power Supply
Dimming	Non-Dimmable	Accessories	Mounting Sleeve Included
IP Rating	IP65	Warranty	3 Years
IK Rating	IK06	Certification	CE, RoHS

ORDERING GUIDE

F21 - 3 - - 120 - BK **Example: F21-3-27-120-BK**

I	Model	Wa	ttage	Color Temp.		Optics		Finish		Optional Accessories
	F21	3	3W	30	2700K 3000K 4000K	120	120°	ВК	Black	Installation Sleeve (Included with fixture)

QUICKSHOP OPTION: F21-3-30-120-BK







PROJECT: PREPARED BY: TYPE:





FLORA CIRCULAR IN-WALL


TERRAIN SERIES

F21

DIMENSIONS







REVISION DATE 10/30/2024 TELEPHONE: 212.931.1230 SUPPORT@RAYHIL.COM WWW.RAYHIL.COM

PROJECT: PREPARED BY: TYPE:



F21

FLORA CIRCULAR IN-WALL

TERRAIN SERIES

NON-DIMMABLE DRIVERS



Model LB55504
Wattage 60W
Dimensions 7.4" x 3.6" x 1.02"
Temperature IP20
Dimming Non-Dimmable



Model LB55450
Wattage 120W
Dimensions 8.66" x 3.6" x 1.61"
Temperature IP20
Dimming Non-Dimmable



Model LB55451
Wattage 200W
Dimensions 10.23" x 4.05" x 1.81"
Temperature IP20
Dimming Non-Dimmable

*Flora Landscape Light Fixture are not compatible with Dimmable Drivers

REVISION DATE 10/30/2024 TELEPHONE: 212.931.1230 SUPPORT@RAYHIL.COM WWW.RAYHIL.COM