



VOR25TMS

VORTEX 2.5 4 HEAD TRIMLESS

2.5" RECESSED LED DOWNLIGHT



FEATURES

- Air-tight and wet location approved
- Type IC rated - approved for direct contact with insulation
- Downlight housing is not required for insulated ceilings
- Quick connect wire allows for efficient installation
- Isolated driver inside junction box
- Optional Emergency Backup
- 5 year warranty

SPECIFICATIONS

Input Voltage	120-277V	Dimming	5% - 100% Triac & 0-10V
Wattage	9W/14W	Lamp Life	50,000hr
Lumens (Delivered)	800LM/1400LM	Environment	IP65 Wet Location
Efficacy(LPW)	>82 lm/W	Material	Aluminum Body with Anodized Heat Sink
Color Temp	18K, 22K, 27K, 30K, 35K, 40K, 50K (CCT adj.)	Operating Temp	-4°F - 104°F
CRI	>90	Cut out	3.42" x 14"
Beam Angle	24° / 38° / 50°		





VOR25TMS

VORTEX 2.5 4 HEAD TRIMLESS

2.5" RECESSED LED DOWNLIGHT

ORDERING GUIDE

VOR25TMS - 4H - _____ - _____ - UNV - _____ - _____ - _____ - _____

Example: VOR25TMS-4H-9-18-UNV-24-HX-WHPWHT-EM

Model	Configuration	Wattage	Color Temp.	Input Voltage	Optics	Lens
VOR25TMS-4H	4H 4 Head	9 9W (800LM) 14 14W (1400LM)	CCT 5CCT Select DTW Dim-Warm (1800K-2200K)	UNV 120-277	24 24° 38 38° 50 50°	HX Hex Louver
Finish	EM					
WHPWHT White Plate/White Trim	EM (Leave Blank for Non-em)					
WHPBKT White Plate/Black Trim						
BKPWHT Black Plate/White Trim	**EM to be functional with 1 head only**					
BKPBKT Black Plate/Black Trim						




***Lead time for the Vortex series on in-stock configuration will be 1 week**



VOR25TMS VORTEX 2.5 4 HEAD TRIMLESS

2.5" RECESSED LED DOWNLIGHT

DIMENSION





VOR25TMS VORTEX 2.5 4 HEAD TRIMLESS

2.5" RECESSED LED DOWNLIGHT

LENS OPTION

Standard Optic



Hex Louver Lens







VOR25TMS VORTEX 2.5 4 HEAD TRIMLESS

2.5" RECESSED LED DOWNLIGHT

4 HEAD DRIVER


Innovative foldable driver simplifies installation
in shallow ceiling conditions






VOR25TMS VORTEX 2.5 4 HEAD TRIMLESS

2.5" RECESSED LED DOWNLIGHT



EMERGENCY BACK UP DRIVER
RAD25/35-EM

90 minute run time
See spec sheet for further information





VOR25TMS

VORTEX 2.5 4 HEAD TRIMLESS

2.5" RECESSED LED DOWNLIGHT

COMPATIBLE DRIVERS

LURTRON	LOAD (W)
SKYLARK CONTOUR LECL-153P	150W
SKYLARK CONTOUR CTCL-150H	150W
SKYLARK CONTOUR LGCL-153PLH	150W
SKYLARK CONTOUR CTCL-153P	150W
SKYLARK CONTOUR SCL-153P	150W
SKYLARK CONTOUR S-600P	600W
CASETA PD-6WCL	600W
CASETA PD-5NE	150W
CASETA PD-10NXD	250W
DIVA DVCL-153P	150W
TOGGLER TGGL-153P	150W
ARIADNI AYCL-153P	150W
MAESTRO MACL-153M	150W

LURTRON	LOAD (W)
ILLUMATEC IPL06	150W
SURESLIDE 6672	150W
SURESLIDE 6674	150W

EATON	LOAD (W)
SMART DIMMER AAL06	300W

PASS & SEYMOUR	LOAD (W)
HARMONY DCL453PTCCCV6	150W

GE	LOAD (W)
ROCKER 10464	150W
TOGGLE 18027	150W