



RAD35 SONIC X ADJUSTABLE

3.5" RECESSED LED DOWNLIGHT



FEATURES

- Air-tight and wet location approved
- Type IC rated - approved for direct contact with insulation
- Universal Voltage and Dimming
- Adjustable Tilt up to 25 Degree
- Quick connect wire allows for efficient installation
- New construction plate available
- Optional Emergency Backup
- 5 Year Warranty

SPECIFICATIONS

Wattage	20W	Dimming	5% - 100% Triac & 0-10V
Lumens (Delivered)	2000LM	Environment	IP65 Wet Location
Input Voltage	120-277V	Material	Aluminum Body with Anodized Heat Sink
CCT	5CCT Select / 1800K - 3000K Dim to Warm	Operating Temperature	-4°F - 104°F
Efficacy	>82LM/W	Lamp Life	50,000 hrs
CRI	>90	Cut Out	4"
Beam Angle	15°/24°/36°/50°		



PROJECT:

PREPARED BY:

TYPE:



RAD35 SONIC X ADJUSTABLE

3.5" RECESSED LED DOWNLIGHT

ORDERING GUIDE

RAD35ADJ -R- 20 - _____ - UNV - _____ - _____ - _____ - _____

Example: RAD35AJD-R-20-CCT-UNV-15-C-WT-EM-CP

Model	Wattage	Color Temperature	Input Voltage	Beam Angle	Lens
RAD35ADJ-R (Round)	20 20W (2000LM)	CCT CCT Adj. (27K, 30K, 35K 40K, 50K) DTW 1800K - 3000K (Dim to Warm)	UNV 120-277V (5%-100% Triac & 0-10V)	15 15° 24 24° 36 36° 50 50°	C Clear F Frosted HX Hex Louver SL Solite
Trim Finish	EM	Protection			
WT White BK Black	None (Leave Blank) EM EM Battery	None (Leave Blank) CP Chicago Plenum			

NEW CONSTRUCTION HOUSING



Model	Description
LB15156	New Construction Housing Plate



RAD35 SONIC X ADJUSTABLE

3.5" RECESSED LED DOWNLIGHT

DIMENSIONS





RAD35 SONIC X ADJUSTABLE

3.5" RECESSED LED DOWNLIGHT


Standard Optic



Hex Louver Lens



Frosted Lens






RAD35 SONIC X ADJUSTABLE

3.5" RECESSED LED DOWNLIGHT

ACCESSORIES

NEW CONSTRUCTION MOUNTING PLATE LB15156


- Constructed out of galvanized steel
- Magnetic plate and driver facilitate easy and secure placement
- Adjustable Hanger Bars up to 24"






RAD35 SONIC X ADJUSTABLE

3.5" RECESSED LED DOWNLIGHT



EMERGENCY BACK UP DRIVER
RAD25/35-EM

90 minute run time
See spec sheet for further information





RAD35 SONIC X ADJUSTABLE

3.5" RECESSED LED DOWNLIGHT

COMPATIBLE DRIVERS

LURTRON	LOAD (W)
SKYLARK CONTOUR LECL-153P	150W
SKYLARK CONTOUR CTCL-150H	150W
SKYLARK CONTOUR LGCL-153PLH	150W
SKYLARK CONTOUR CTCL-153P	150W
SKYLARK CONTOUR SCL-153P	150W
SKYLARK CONTOUR S-600P	600W
CASETA PD-6WCL	600W
CASETA PD-5NE	150W
CASETA PD-10NXD	250W
DIVA DVCL-153P	150W
TOGGLER TGGL-153P	150W
ARIADNI AYCL-153P	150W
MAESTRO MACL-153M	150W

LURTRON	LOAD (W)
ILLUMATEC IPL06	150W
SURESLIDE 6672	150W
SURESLIDE 6674	150W

EATON	LOAD (W)
SMART DIMMER AAL06	300W

PASS & SEYMOUR	LOAD (W)
HARMONY DCL453PTCCCV6	150W

GE	LOAD (W)
ROCKER 10464	150W
TOGGLE 18027	150W