



RYNO 3.0 ADJUSTABLE MILLWORK

3" RECESSED LED DOWNLIGHT



FEATURES

- Selectable wattage (9W / 12W / 15W) with high-efficacy output for flexible performance across applications.
- Precision optics available in 8°, 15°, 24°, 36°, and 50° beam spreads for controlled illumination.
- Universal voltage (120–277V) with Triac/0-10V dimming from 1–100% for smooth control.
- Compact 3" aperture with 360 degree rotation and 30 degree tilt.
- Type IC rated - approved for direct contact with insulation.

PERFORMANCE

Wattage	9W/12W/15W Selectable
Lumens (Delivered)	Up to 117LM/W
Input Voltage	120-277V
Dimming	Triac, 0-10V (1%-100%)
Lifetime	50,000 hrs

LIGHT SOURCE

CCT	2700K/3000K/3500K/4000K/Dim to Warm
CRI	90

OPTICS

Lens / Reflector	8° / 15° / 24° / 36° / 50°
------------------	----------------------------

MEDIA

Hex Louver
Solite
Linear Spread
Asymmetric
Double Asymmetric

CERTIFICATION

IC Rated
ETL
CETL
Title 24
FCC

APPLICATION

Environment	Wet Location
Material	Aluminum
Operating Temperature	-49° F to 113° F
Lamp Life	5 Years
Cut Out	3.25"
Tilt	30 Degree
Rotation	360 Degree

SUPPORTIVE FILE (WEBSITE LINK)

[IES File](#)
[Installation Guide](#)
[Trimmed Configuration](#)
[Trimless Mud-In Configuration](#)
[Millwork Configuration](#)
[Wallwash Configuration](#)
[Adjustable Trimmed Configuration](#)
[Adjustable Trimless Mud-In Configuration](#)

PROJECT:

PREPARED BY:

TYPE:



RYNO 3.0 ADJUSTABLE MILLWORK

3" RECESSED LED DOWNLIGHT

ORDERING GUIDE

RYN23- _____ - _____ - _____ - _____

Example: RYN23-2790-15-L-HX-3ADJRMLWK-WT

** New Construction Plate is an individual part number NCH-RYN23

Component	Component Code	Component Detail
 ENGINE	RYN23	9W/12W/15W Engine
 CHIP	2790 3090 3590 4090 DTW 2090-8L 3090-8L 3590-8L 4090-8L	2700K, 90CRI 3000K, 90CRI 3500K, 90CRI 4000K, 90CRI 1800-3000K Dim to Warm, 98CRI 2700K, 90CRI 8 Degree Narrow 3000K, 90CRI 8 Degree Narrow 3500K, 90CRI 8 Degree Narrow 4000K, 90CRI 8 Degree Narrow
 Reflector Lens OPTIC	8 15 24 36 50 L R	8 Degree ** For use with 8 degree chip only 15 Degree 24 Degree 36 Degree 50 Degree
 Solite Hex Louver LS / AS / DA MEDIA	HX SL LS AS DA	Hex Louver (Leave blank for none) Solite (SL-HX for multiple Media sequence) Linear Spread Asymmetric Double Asymmetric
 TRIM	3ADJRMLWK-WT 3ADJRMLWK-BK	Adjustable Round Millwork Trim, White Finish Adjustable Round Millwork Trim, Black Finish
	NCH-RYN23	New Construction Plate **Individual part number from downlight

PROJECT:

PREPARED BY:



TYPE:



RYNO 3.0 ADJUSTABLE MILLWORK

3" RECESSED LED DOWNLIGHT

DIMENSIONS





RYNO 3.0 ADJUSTABLE MILLWORK

3" RECESSED LED DOWNLIGHT

DELIVERED LUMENS MATRIX

90CRI, Lens Optic, White Trim

Wattage	Color Temperature	15° Optic	24° Optic	36° Optic	50° Optic
9W	2700K (90CRI)	1023.9	1072.2	1016.2	966
	3000K (90CRI)	957.4	996.08	952.72	925.7
	3500K (90CRI)	1073.86	1013	1006.22	999.02
	4000K (90CRI)	1101.06	1150.49	1093.15	1028.06
	Dim to Warm (98CRI)	702.99	720.2	684.69	662.4
	Hex Louver (3000K)	771.7	744.24	722.72	646.01
	Solite (3000K)	912.8	931.22	899.57	869.68
12W	2700K (90CRI)	1347.2	1423.7	1417.5	1397.7
	3000K (90CRI)	1453	1334.6	1354.5	1297.9
	3500K (90CRI)	1369.6	1406.3	1428.3	1356
	4000K (90CRI)	1401.9	1453.3	1451	1403.6
	Dim to Warm (98CRI)	1057.5	1075.3	1062.2	1051.4
	Hex Louver (3000K)	1068.2	1100.5	1073.3	863.4
	Solite (3000K)	1352.3	1383.7	1402.5	1335.5
15W	2700K (90CRI)	1537.5	1594.8	1588	1519.5
	3000K (90CRI)	1635.1	1658.6	1688.9	1610.7
	3500K (90CRI)	1699.6	1731	1754.5	1700.1
	4000K (90CRI)	1760	1890.7	1790.9	1741.7
	Dim to Warm (98CRI)	1368.3	1370.7	1383.2	1334
	Hex Louver (3000K)	1198.9	1213.6	1198.7	1068.8
	Solite (3000K)	1508	1566.1	1587.3	1491.2





RYNO 3.0 ADJUSTABLE MILLWORK

3" RECESSED LED DOWNLIGHT



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

9W





C0(Max):
C0/C180:
C90/C270:
Field angle(10%Imax):C0/180Left:37.8 Right:27.8
:C90/270Left:30.1 Right:30.1
Beam Angle(50%Imax):C0/180Left:26.5 Right:16.5
:C90/270Left:21.2 Right:21.2

12W



C15(Max):
C0/C180:
C90/C270:
Field angle(10%Imax):C0/180Left:31.0 Right:31.0
:C90/270Left:30.9 Right:30.9
Beam Angle(50%Imax):C0/180Left:21.2 Right:21.2
:C90/270Left:21.2 Right:21.2

15W



C15(Max):
C0/C180:
C90/C270:
Field angle(10%Imax):C0/180Left:31.0 Right:31.0
:C90/270Left:30.9 Right:30.9
Beam Angle(50%Imax):C0/180Left:21.2 Right:21.2
:C90/270Left:21.2 Right:21.2




RYNO 3.0 ADJUSTABLE MILLWORK

3" RECESSED LED DOWNLIGHT

NEW CONSTRUCTION MOUNTING PLATE NCH-RYN23

- Constructed out of galvanized steel





RYNO 3.0 ADJUSTABLE MILLWORK

3" RECESSED LED DOWNLIGHT

COMPATIBLE DRIVERS

LUTRON	LOAD (W)
LUTRON MC3J2	300W
LUTRON AYCL-153P	150W
LUTRON SCL-153P	150W
LUTRON DVCL-153P	150W
LUTRON DVSTV-453P	450W

LEVITON	LOAD (W)
LEVITON IPL06	300W
LEVITON 6672	300W
LEVITON 6674	150W
LEVITON DSM10	450W
LEVITON IP710	—

LEGRAND	LOAD (W)
LEGRAND/PS RHCL453P	450W