


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 117.45 lm/W			
MODEL		Imax(cd)	2791	S/MH(C0/180)	0.59
NOMINAL POWER(W)	12	LOR(%)	100.0	S/MH(C90/270)	0.63
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	1241.1	η UP,DN(C0-180)	0.0,46.9
NOMINAL FLUX(lm)	1241.07	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,53.1
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE(V)	120	η down(%)	100.0	CIBSE SHR MAX	0.60

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CHEN
Test Date:2026-06-26

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	2403	2364	2235	2211	2348	2535	2499	2422	0- 10	246.8	246.8	19.9,19.9
20	1277	1206	1070	1028	1171	1354	1368	1286	10- 20	501.0	747.8	60.3,60.3
30	376.0	352.6	298.9	293.1	342.5	408.2	421.8	394.7	20- 30	325.7	1074	86.5,86.5
40	85.82	81.18	67.27	60.16	76.53	90.83	93.51	83.53	30- 40	113.8	1187	95.7,95.7
50	27.68	27.63	23.20	22.58	25.22	29.17	29.81	27.68	40- 50	35.53	1223	98.5,98.5
60	6.522	9.031	5.629	7.306	5.640	9.462	7.398	10.07	50- 60	14.09	1237	99.7,99.7
70	1.127	1.258	0.6385	0.9329	0.7105	1.435	1.451	1.691	60- 70	3.630	1241	100,100
80	0.0726	0.0611	0.0612	0.0611	0.1387	0.1216	0.1190	0.1281	70- 80	0.3375	1241	100,100
90	0.0611	0.0649	0.0650	0.0649	0.1413	0.1261	0.1223	0.1222	80- 90	0.1015	1241	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1209.2 lm

%lum = 97.4%

%lamp = 97.4%

Conical surface Flux(120deg): 1237 lm

%lum = 99.7%


%lamp = 99.7%

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CHEN
 Test Date:2026-06-26

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:5.620m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	132	132
80	79	66
75	64	55
70	620	351
65	1396	1244
60	2452	2115
55	4985	3798
50	8097	6782
45	12275	10091


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CHEN
Test Date:2026-06-26

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.12	1.10	1.08	1.10	1.08	1.06	1.06	1.04	1.03	1.02	1.01	.00	.99	.98	.97	.95
2.0	1.05	1.02	.99	1.04	1.01	.98	1.01	.98	.96	.98	.95	.94	.95	.93	.92	.90
3.0	.00	.95	.92	.98	.94	.91	.96	.92	.90	.93	.91	.88	.91	.89	.87	.86
4.0	.94	.90	.86	.93	.89	.86	.91	.88	.85	.89	.86	.84	.88	.85	.83	.81
5.0	.90	.85	.81	.89	.84	.81	.87	.83	.80	.86	.82	.79	.84	.81	.79	.77
6.0	.86	.80	.77	.85	.80	.77	.83	.79	.76	.82	.78	.76	.81	.78	.75	.74
7.0	.82	.77	.73	.81	.76	.73	.80	.76	.72	.79	.75	.72	.78	.74	.72	.71
8.0	.78	.73	.70	.78	.73	.69	.77	.72	.69	.76	.72	.69	.75	.71	.69	.67
9.0	.75	.70	.67	.74	.70	.66	.74	.69	.66	.73	.69	.66	.72	.68	.66	.65
10.0	.72	.67	.64	.71	.67	.64	.71	.66	.63	.70	.66	.63	.69	.66	.63	.62



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CHEN
Test Date:2026-06-26

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.157	.089	.028	.151	.086	.027	.138	.079	.025	.127	.073	.023	.116	.067	.022		
2.0	.149	.081	.025	.143	.079	.024	.133	.074	.023	.123	.069	.022	.114	.065	.020		
3.0	.140	.075	.022	.136	.073	.022	.127	.069	.021	.119	.065	.020	.111	.062	.019		
4.0	.133	.069	.020	.129	.067	.020	.121	.064	.019	.114	.061	.019	.108	.059	.018		
5.0	.126	.064	.019	.123	.063	.018	.116	.061	.018	.110	.058	.017	.105	.056	.017		
6.0	.120	.060	.017	.117	.059	.017	.112	.057	.017	.106	.055	.016	.101	.053	.016		
7.0	.115	.057	.016	.112	.056	.016	.107	.054	.016	.102	.053	.015	.098	.051	.015		
8.0	.110	.054	.015	.107	.053	.015	.103	.051	.015	.099	.050	.014	.095	.049	.014		
9.0	.105	.051	.014	.103	.050	.014	.099	.049	.014	.095	.048	.014	.092	.047	.013		
10.0	.101	.048	.013	.099	.048	.013	.095	.047	.013	.092	.046	.013	.089	.045	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.170	.157	.146	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016		
2.0	.153	.133	.115	.131	.114	.100	.090	.079	.070	.052	.046	.041	.017	.015	.013		
3.0	.140	.113	.093	.120	.098	.080	.082	.068	.056	.047	.040	.033	.015	.013	.011		
4.0	.128	.098	.076	.110	.085	.066	.076	.059	.046	.044	.035	.027	.014	.011	.009		
5.0	.119	.086	.063	.102	.075	.055	.070	.052	.038	.041	.031	.023	.013	.010	.008		
6.0	.111	.077	.053	.095	.067	.046	.066	.047	.032	.038	.027	.019	.012	.009	.006		
7.0	.104	.069	.045	.089	.060	.039	.062	.042	.028	.036	.025	.016	.012	.008	.005		
8.0	.098	.063	.038	.084	.054	.033	.058	.038	.024	.034	.022	.014	.011	.007	.005		
9.0	.092	.057	.033	.080	.050	.029	.055	.035	.021	.032	.021	.012	.010	.007	.004		
10.0	.088	.053	.029	.076	.046	.026	.052	.032	.018	.031	.019	.011	.010	.006	.004		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CHEN
Test Date:2026-06-26

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: LB10000-CCT					TYPE:CRI90 5000K					WEIGHT:				
SPEC.:					DIM.:					SERIAL No.:1				
MFR.:					SUR.:73*73MM					Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H					13.9	14.7	14.1	14.8	15.0	12.8	13.6	13.0	13.8	13.9
3H					13.7	14.5	14.0	14.7	14.9	12.7	13.4	12.9	13.6	13.8
4H					13.7	14.4	13.9	14.6	14.8	12.6	13.3	12.9	13.5	13.7
6H					13.6	14.2	13.9	14.5	14.7	12.5	13.2	12.8	13.4	13.7
8H					13.5	14.2	13.8	14.4	14.7	12.5	13.1	12.8	13.4	13.6
12H					13.5	14.1	13.8	14.3	14.6	12.4	13.0	12.7	13.3	13.6
4H 2H					13.7	14.4	14.0	14.6	14.8	12.7	13.4	12.9	13.6	13.8
3H					13.5	14.2	13.9	14.4	14.7	12.5	13.1	12.8	13.4	13.7
4H					13.4	14.0	13.8	14.3	14.6	12.4	13.0	12.8	13.3	13.6
6H					13.3	13.8	13.7	14.2	14.5	12.3	12.8	12.7	13.1	13.5
8H					13.3	13.7	13.7	14.1	14.5	12.3	12.7	12.7	13.1	13.4
12H					13.2	13.7	13.6	14.0	14.4	12.2	12.6	12.6	13.0	13.4
8H 4H					13.3	13.7	13.7	14.1	14.5	12.3	12.7	12.7	13.1	13.4
6H					13.2	13.6	13.6	14.0	14.4	12.2	12.5	12.6	12.9	13.3
8H					13.1	13.5	13.6	13.9	14.3	12.1	12.4	12.6	12.9	13.3
12H					13.1	13.4	13.5	13.8	14.3	12.1	12.3	12.5	12.8	13.2
12H 4H					13.2	13.7	13.6	14.0	14.4	12.2	12.6	12.6	13.0	13.4
6H					13.1	13.5	13.6	13.9	14.3	12.1	12.4	12.6	12.9	13.3
8H					13.1	13.4	13.5	13.8	14.3	12.1	12.3	12.5	12.8	13.2
Variations with the observer position at spacings:														
S = 1.0H					+ 3.0 / - 6.7					+ 2.5 / - 6.8				
1.5H					+ 4.4 / - 3.9					+ 3.6 / - 3.4				
2.0H					+ 4.3 / - 6.6					+ 4.0 / - 6.0				

CIE Pub.117, 1241 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 0.8$)

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CHEN
 Test Date:2026-06-26

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:5.620m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	83	79	88	83	79	88	82	79	75
0.80	96	91	87	95	90	87	94	90	86	83
1.00	100	95	92	99	95	91	98	94	91	87
1.25	104	99	96	103	99	95	101	97	95	91
1.50	107	102	99	105	101	99	103	100	97	93
2.00	109	105	102	108	104	101	105	102	100	95
2.50	111	107	104	109	106	103	106	104	101	96
3.00	112	109	106	110	108	105	107	105	103	97
4.00	114	112	109	112	110	108	109	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: CHEN
 Test Date: 2026-06-26

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 5.620m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CHEN
Test Date:2026-06-26

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

AAI Figure

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CHEN
Test Date:2026-06-26

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CHEN
Test Date:2026-06-26

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	1313
L_0~180 (75) av	92
L_0~180 (85) av	214
L_90~270 (65) av	1459
L_90~270 (75) av	72
L_90~270 (85) av	197
L_45 (65) av	1654
L_45 (75) av	130
L_45 (85) av	199

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CHEN
Test Date:2026-06-26

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: CHEN
Test Date: 2026-06-26

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 5.620m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:

UNIT: cd

[illegible]

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: LB10000-CCT	TYPE:CRI90 5000K	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.:	SUR.:73*73MM	Shielding Angle:

UNIT: cd

[illegible]

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:5.620m [K=1.0000]
Remarks:

```